

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/013257 A2

- (51) International Patent Classification⁷: G10C
- (21) International Application Number:
PCT/US2004/024486
- (22) International Filing Date: 26 July 2004 (26.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/490,077 25 July 2003 (25.07.2003) US
- (71) Applicant and
(72) Inventor: SHARMA, Ravi, Ivan [US/US]; 404 Park Avenue South, New York, NY 10016 (US).

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- (74) Agent: POLLACK, Grant, E., Esq.; Steinberg & Raskin, P.C., 1140 Avenue of the Americas, 15th Floor, New York, NY 10036 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

(54) Title: INVERTED KEYBOARD INSTRUMENT AND METHOD OF PLAYING THE SAME



(57) Abstract: An electronic keyboard instrument is provided and methods of playing and assembling the same. The instrument comprises a controller for enabling activation of electronic signals having audible, visible, amplifiable, recordable and/or like characteristics, and a power source for operating the controller. A first keyboard is provided having a first selected length and being oriented in a first direction such that (i) audible notes of music from at least one internal sound module and/or at least one external sound module, (ii) recordable data to be enhanced or modified by an external sequencer or program controlled apparatus, (iii) photoelectric signals, and (iv) processes or mechanisms, triggered or controlled by external signals or data, for controlling machines, video playback or lighting, and/or the like may be generated and/or activated using a first hand of one or more users. A second keyboard with a second selected length is generally coextensive with and oriented generally opposite to the first such that (i) audible notes of music from at least one internal sound module and/or at least one external sound module, (ii) recordable data to be enhanced or modified by an external sequencer or program controlled apparatus, (iii) photoelectric signals, and (iv) processes or mechanisms, triggered or controlled by external signals or data, for controlling machines, video playback or lighting, and/or the like may be generated and/or activated using a second hand of the one or more users. In addition, an interface connects the controller to at least one external device having sound module, and/or sequencing and signal enhancement functions. A plurality of peripheral devices operatively connected thereto permit interactive control and manipulation of the signals. Finally, a wearable support is mounted to the instrument for suspending the first and second keyboards from the user's body during instrument operation. Alternatively, the instrument is suspended by a support structure in a generally horizontal fashion for simultaneous operation by multiple users.